

GESEL HEINZ TOP ENERGY H2 SAE 5W-40

Multifunctional High Performance Engine Oil

Product description

GESEL HEINZ TOP ENERGY H2 SAE 5W-40 is a top quality, state-of-the-art low friction engine oil for vehicles with gasoline or diesel engines with and without diesel particulate filters (DPF). The unique composition of selected base oils, using synthetic technology, together with a modern additive package provides its outstanding performance level. GESEL HEINZ TOP ENERGY H2 SAE 5W-40 provides exceptional protection against wear and reduces oil as well as fuel consumption. It allows oil drain intervals of up to 30.000 km, depending on the car manufacturer's specification. The low viscosity grade secures an excellent cold-start behaviour and fast lubrication of all engine parts.

Product advantages

- Fuel economy due to low-viscosity characteristics.
- Reliable cold-start behaviour and quick lubrication of the engine, even under very low temperatures.
- Extended oil drain intervals because of excellent oxidation stability and low evaporation loss.
- High cleaning power due to very good detergency and dispersion properties.
- Very strong protection against wear, corrosion and foaming.
- Stable lubricating film even at high temperatures and under excessive loads.

Typical properties

| Parameter | Method | Unit | GESEL HEINZ H2 SAE 5W-40 |
|-----------------------------|--------------|--------------------|--------------------------|
| Density at 15 °C | DIN EN ISO | Kg/m ³ | 856 |
| Viscosity, kinematic 100 °C | DIN 51562-1 | mm ² /s | 14,3 |
| Viscosity, kinematic 40 °C | DIN 51562-1 | mm ² /s | 88,9 |
| Flash Point COC | DIN ISO 2592 | °C | > 200 |
| Pour Point | DIN ISO 3016 | °C | -39 |
| Viscosity Index | DIN ISO 2909 | | 167 |

Specifications

API SN/CF
ACEA A3/B4

Meets the requirements of:

MB 229.3/226.5, VW 502 00 / 505 00, Porsche A40, BMW Longlife-01, Renault RN 0700 / RN 0710, PSA B71 2296, Opel GM-LL-B-025

Storage recommendation

All packings should be stored in roofed conditions. In those cases, where an in-house storage is not possible, it is advisable, that a cover prevents water or dirt from penetrating into the packing. Please store products not over a temperature of 60 °C (if possible store under cool conditions, but frost-protected).

GESEL HEINZ SUPER ENERGY H2 SAE 5W-40

January 1st, 2019

GESEL HEINZ and the GESEL HEINZ Logo are property of Gesol Technologies GmbH, Germany, and their use is licensed.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility is taken by Gesol Technologies GmbH for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.