

GESEL HEINZ TOP ENERGY H6 SAE 0W-20

High Performance Engine Oil for Asian and American Vehicles

Product description

GESEL HEINZ TOP ENERGY H6 0W-20 is a high performance, low SAPS, HC-synthetic oil with special additives. It is used where lubricity characteristics of motor oils with the viscosity class SAE 0W-20 are required and has been especially developed for the year-round use in Asian and American vehicles. It is fuel efficient and ensures excellent performance even under hardest conditions. GESEL HEINZ TOP ENERGY H6 0W-20 is ideal for modern Japanese, Korean and American petrol engines, particularly suitable for hybrid vehicles and ECO engines. It provides a stable lubricating film for safe wear protection, even with hot oil and under excessive loads. It shows excellent performance when used at full power, as well as during severe weather conditions.

Product advantages

- Safe cold start and quick lubrication of the engine, even at low temperatures.
- Running smoothly and reduces engine noise as well as fuel consumption.
- Excellent wear protection and highest oxidation stability due Group III base oils and an advanced additive package.
- Excellent engine cleanness.
- Safer year-round operation due to outstanding viscosity-temperature behaviour and high shear stability.
- Low oil consumption due to a very low evaporation loss.

Typical properties

Parameter	Method	Unit	GESEL HEINZ H6 SAE 0W-20
Density at 15 °C	DIN EN ISO 12185	Kg/m ³	857
Viscosity, kinematic 100 °C	DIN 51562-1	mm ² /s	8,40
Viscosity, kinematic 40 °C	DIN 51562-1	mm ² /s	45,0
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	-42
Viscosity Index	DIN ISO 2909		167

Specifications

API SN
ILSAC GF-5

Recommended for Honda, Hyundai, Kia, Mazda, Mitsubishi, Nissan, Suzuki, Toyota, Subaru, GM, Ford WSS-M2C 930-A, Ford WSS-M2C 925-A, Chrysler MS-6395.

Storage recommendation

All packings should be stored in roofed conditions. In those cases, where an in-house storage is not possible, it is advisable, that a cover prevents water or dirt from penetrating into the packing. Please store products not over a temperature of 60 °C (if possible store under cool conditions, but frost-protected).

GESEL HEINZ SUPER ENERGY H6 SAE 0W-20

January 1st, 2019

GESEL HEINZ and the GESEL HEINZ Logo are property of Gesol Technologies GmbH, Germany, and their use is licensed.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version if this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility is taken by Gesol Technologies GmbH for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.