

# GESEL HEINZ XMF L2 SAE 10W-40

## Modern Heavy Duty Diesel Engine Oil

### Product description

GESEL HEINZ XMF L2 SAE 10W-40 is a state-of-the-art Super High-Performance Diesel (SHPD) engine oil produced using HC synthetic oils and advanced additives. GESEL HEINZ XMF L2 SAE 10W-40 is particularly suitable for vehicles equipped with Otto and Diesel engines, with or without turbocharging. It is used in mixed vehicle fleets in engines from different manufacturers according to the manufacturer's specification. Its modern design makes a wide range of applications possible and ensures safe operation under all operating conditions.

### Product advantages

- Suitable for both passenger cars and commercial vehicles, as well as agricultural and construction machinery.
- It combines the specifications of European, American and Japanese manufacturers.
- Prevents adhesion, lacquering and coking of cylinders, pistons, valves and turbochargers in a reliable manner.
- Safer year-round operation due to outstanding viscosity-temperature behaviour and high shear stability.
- Very low oil consumption and high level of oxidation protection.
- Reliable protection against 'black sludge'.

### Typical properties

Parameter	Method	Unit	GESEL HEINZ XMF L2 SAE 10W-40
Density at 15 °C	DIN EN ISO 12185	Kg/m <sup>3</sup>	868
Viscosity, kinematic 100 °C	DIN 51562-1	mm <sup>2</sup> /s	14,7
Viscosity, kinematic 40 °C	DIN 51562-1	mm <sup>2</sup> /s	94,2
Flash Point COC	DIN ISO 2592	°C	> 210
Pour Point	DIN ISO 3016	°C	-36
Viscosity Index	DIN ISO 2909		163

### The quality of this product is equivalent to EU regulations

API SL  
API CI-4  
ACEA E7, ACEA A3/B4, ACEA A3/B3  
MB 228.3, MB 229.1, DEUTZ DQC III-10, MAN M 3275-1,  
MTU Type 2, VOLVO VDS-3, Renault RDL-2, MACK-EO-N,  
JASO DH-1, Allison C4, Cummins CES 20077, 20078, Voith A

### Storage recommendation

All packings should be stored in roofed conditions. In those cases, where an in-house storage is not possible, it is advisable, that a cover prevents water or dirt from penetrating into the packing. Please store products not over a temperature of 60 °C (if possible store under cool conditions, but frost-protected).

GESEL HEINZ XMF L2 SAE 10W-40

January 1<sup>st</sup>, 2019

GESEL HEINZ and the GESEL HEINZ Logo are property of Gesol Technologies GmbH, Germany, and their use is licensed.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility is taken by Gesol Technologies GmbH for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.